




# Contact Smart Card Readers

For ISO-7816 Compliant Smart Cards

## Specifications

	R301 USB	R301 Stand	R301 SIM
			
Description	A stylish USB desktop card reader supporting ISO-7816 contact smart cards.	A robust USB desktop card reader that takes a smart card inserted vertically.	A USB smart card reader for SIM cards (Subscriber Identity Modules).
Supported Cards	ISO-7816 cards <ul style="list-style-type: none"><li>• T=0 and T=1 protocols</li><li>• Class A, B and C</li></ul>	ISO-7816 cards <ul style="list-style-type: none"><li>• T=0 and T=1 protocols</li><li>• Class A, B and C</li></ul>	ISO-7816 cards <ul style="list-style-type: none"><li>• T=0 and T=1 protocols</li><li>• Class A, B and C</li></ul>
Case Style	C25	C41	B6
Card Types	1.8V, 3V and 5V	1.8V, 3V and 5V	1.8V, 3V and 5V
Card Size	ISO 7810 ID-1	ISO 7810 ID-1	ISO 7810 ID-000 (GSM 11.11)
Power to Card	60 mA	60 mA	60 mA
Smart Card Clock Frequency	4 MHz - 12 MHz	4 MHz - 12 MHz	4 MHz - 12 MHz
Smart Card Interface Speed	10753 bps ~ 625 kbps	13440 bps ~ 625 kbps	10753 bps ~ 625 kbps
Dimensions	74 x 56 x 11 mm	120 x 80 x 76 mm	56 x 21 x 7.5 mm
Weight	46.7 g	296 g	11 g
Durability	100,000 insertions	300,000 insertions	100,000 insertions
Contact Principle	Friction technology	Landing contact technology	Friction technology

	<b>R301 USB</b>	<b>R301 Stand</b>	<b>R301 SIM</b>
Host Interface	USB 2.0	USB 2.0	USB 2.0
Working Current	< 50 mA	< 50 mA	< 50 mA
Working Temperature	0 °C ~ 60 °C	0 °C ~ 60 °C	0 °C ~ 60 °C
Storage Temperature	-20 °C ~ 85 °C	-20 °C ~ 85 °C	-20 °C ~ 85 °C
Humidity Rating	≤90% (non-condensed)	≤90% (non-condensed)	≤90% (non-condensed)
Manufacturer	Feitian	Feitian	Feitian
Supported Standards	<ul style="list-style-type: none"> <li>• PC/SC</li> <li>• CCID</li> <li>• EMV Level 1</li> <li>• Microsoft WHQL</li> <li>• GSA FIPS 201 APL</li> </ul>	<ul style="list-style-type: none"> <li>• PC/SC</li> <li>• CCID</li> <li>• EMV Level 1</li> <li>• Microsoft WHQL</li> <li>• GSA FIPS 201 APL</li> </ul>	<ul style="list-style-type: none"> <li>• PC/SC</li> <li>• CCID</li> <li>• EMV Level 1</li> <li>• Microsoft WHQL</li> <li>• GSA FIPS 201 APL</li> </ul>
Compliance	RoHS, CE, FCC	RoHS, CE, FCC	RoHS, CE, FCC
Supported Platforms	<ul style="list-style-type: none"> <li>• Windows - Windows 2000 and newer</li> <li>• macOS and OS X</li> <li>• Linux</li> <li>• Android <ul style="list-style-type: none"> <li>◦ 4.0 onwards</li> <li>◦ Device must support USB On-The-Go</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>• Windows - Windows 2000 and newer</li> <li>• macOS and OS X</li> <li>• Linux</li> <li>• Android <ul style="list-style-type: none"> <li>◦ 4.0 onwards</li> <li>◦ Device must support USB On-The-Go</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>• Windows - Windows 2000 and newer</li> <li>• macOS and OS X</li> <li>• Linux</li> <li>• Android <ul style="list-style-type: none"> <li>◦ 4.0 onwards</li> <li>◦ Device must support USB On-The-Go</li> </ul> </li> </ul>